

AC 300®

Wall coating - white

Product description:

AC 300 is a ready-to-use, matt, solvent-free 1-component coating with a PU acrylate base. Suitable for indoors and outdoors.

Application:

AC 300 can be used universally thanks to its very high adhesion, e.g. in stables and for coating facades.

AC 300 is applied in **two** coats (roller or brush application)!

Properties:

Weather and abrasion resistant. Wet abrasion class

2. Easy to apply, high hiding power

White, non-yellowing.

High filling capacity, low stress, resistant to ageing with minimal chalking. Very high diffusion capacity and moisture repellence on the surface.

AC 300 wall coating is designed to prevent the formation of mould, moss and algae.

Substrate condition:

Suitable for any properly prepared, well adhering surface that is free from grease and other separating agents.

Always clean the surface to be coated with AC 600 special cleaner beforehand.

Comments:

Do not dilute with water!

Do not add colour!

Cleaning the tools:

Wash immediately after use using water. Leave the equipment in the coating during breaks to avoid it drying out.

Technical data:

Colour shade	:	white
Mixing ratio	:	1-component
Density at 23 °C and 50% relative humidity	:	1.3 - 1.5 g/cm ³
Viscosity	:	viscous
Dust dry after roller application at 20 °C	:	approx. 60 min
Can be recoated/second coat (at 20 °C)	:	approx. 2 hours.
Cured completely (at 20 °C)	:	approx. 24 hours
Minimum working temperature	:	air and surface at 10 °C
Material consumption	:	min. 300 g/m ² Approximate value for two coats!
Container size	:	15.0 kg
Storage	:	Cool and dry, but frost-free, approx. 1 year in unopened original container.
Solid body content	:	68%
Base	:	PU acrylate base

We reserve the right to make technical changes in the course of further development. This technical data sheet is only intended to provide non-binding advice. As the application and handling of this product is beyond our control and the various types of surfaces and stresses may have an influence on the choice of application method, our advice, whether given verbally, in writing or by means of trials, does not exempt the user from having to test the suitability of our building material for the intended purpose. This also applies to the protection of third party property rights as well as to applications and methods which are not expressly specified by us in writing.

The publication of this leaflet renders all previous leaflets invalid.